

产品一览表

■ 小型铝电解电容器

系列名	用途	工作上限温度 标准寿命 (Hrs)	小型	标准品	低阻抗	长寿命	耐溶剂	端子类型	额定电压范围 (V _{DC})	容量范围 (μF)	页	
小型	低阻抗 低ESR	NXL(LXV)	低阻抗,长寿命	105°C	2,000~5,000hrs	●	●	●	引线	6.3~100	1~15,000	113
		NXP(LXZ)	低阻抗,长寿命	105°C	2,000~5,000hrs	●	●	●	引线	6.3~50	22~18,000	116
		NXR	低阻抗,长寿命	105°C	4,000~7,000hrs	●	●	●	引线	6.3~35	330~12,000	118
		NXA	低阻抗,长寿命	105°C	4,000~10,000hrs	●	●	●	引线	6.3~100	1~18,000	120
		NXB	超低阻抗,长寿命	105°C	2,000~5,000hrs	●	●	●	引线	6.3~120	1~8,200	123
		NXK	低阻抗,长寿命,高纹波	105°C	4,000~5,000hrs	●	●	●	引线	10~50	100~2,700	126
		NXH	低阻抗,长寿命	105°C	6,000~10,000hrs	●	●	●	引线	6.3~100	2.2~10,000	128
		NXQ	低阻抗,长寿命,高纹波	105°C	6,000~10,000hrs	●	●	●	引线	6.3~120	8.2~8,200	131
		NXE	超低ESR,长寿命	105°C	3,000~4,000hrs	●	●	●	引线	6.3~35	150~3,300	134
	NXG	超低ESR,长寿命,高纹波	105°C	3,000~4,000hrs	●	●	●	引线	6.3~35	150~3,300	136	
	高信赖性	MLB	长寿命	85°C	8,000hrs	●	●	●	引线	400~500	10~150	138
		MLC	长寿命	85°C	10,000hrs	●	●	●	引线	400~500	10~150	140
		NZE	高纹波	105°C	2,000hrs	●	●	●	引线	160~500	3.3~390	142
		NFC	长寿命,高纹波	105°C	2,000~5,000hrs	●	●	●	引线	160~500	1~330	145
		NFK	长寿命,高纹波	105°C	5,000hrs	●	●	●	引线	160~500	4.7~330	148
		NFS	长寿命,高纹波	105°C	5,000hrs	●	●	●	引线	200~500	6.8~150	151
		NBA	长寿命,高纹波,低温度	105°C	3,000~5,000hrs	●	●	●	引线	160~500	1~470	153
		NBR	长寿命,高纹波,低温度	105°C	3,000~5,000hrs	●	●	●	引线	160~500	1~470	155
		NFA	长寿命,高纹波	105°C	7,000~10,000hrs	●	●	●	引线	160~500	2.2~330	157
		NFL	长寿命,高纹波	105°C	8,000~12,000hrs	●	●	●	引线	160~500	3.3~470	160
NFR		长寿命,高纹波	105°C	8,000~12,000hrs	●	●	●	引线	160~500	1~470	163	
特殊用途	NBC	长寿命,高纹波,低温度	105°C	5,000~12,000hrs	●	●	●	引线	160~500	1~470	166	
	NBL	长寿命,高纹波,低温度	105°C	12,000~20,000hrs	●	●	●	引线	160~500	3.3~470	168	
	NLA	长寿命	105°C	4,000~10,000hrs	●	●	●	引线	6.3~50	10~18,000	170	
	NLC	长寿命	105°C	10,000hrs	●	●	●	引线	6.3~100	1~680	172	
	PXB	宽温度,低阻抗,长寿命	125°C	2,000~5,000hrs	●	●	●	引线	10~450	1~4,700	174	
	PXD	宽温度,超低阻抗,长寿命	125°C	2,000~4,000hrs	●	●	●	引线	10~50	10~4,700	176	
	PXG	宽温度,低阻抗,尺寸缩小品,高纹波	125°C	3,000hrs	●	●	●	引线	10~100	68~8,200	178	
	PFA	宽温度	135°C	2,000hrs	●	●	●	引线	10~100	180~14,000	180	
	PHA	宽温度	150°C	2,000Hrs	●	●	●	引线	10~50	100~3,300	182	
	AHS	音频级	85°C	2,000hrs	●	●	●	引线	10~100	1~10,000	184	
PHL	闪光灯用	5~35°C	5,000times	●	●	●	引线	300~330	5~160	186		
NZD	安全气囊	105°C	5,000hrs	●	●	●	引线	25~35	1,100~15,000	187		

■ 大型铝电解电容器

系列名	用途	工作上限温度 标准寿命 (Hrs)	小型	标准品	低阻抗	长寿命	耐溶剂	端子类型	额定电压范围 (V _{DC})	容量范围 (μF)	页	
一般用途	RDC	超小型化品	85°C	2,000hrs	●	●	●	Pin	16~500	68~56,000	189	
	TDA	小型化品	105°C	2,000hrs	●	●	●	Pin	16~500	47~47,000	193	
	TDC	超小型化品	105°C	2,000hrs	●	●	●	Pin	160~500	68~1,200	197	
	TEA	高度 15mm	105°C	2,000hrs	●	●	●	Pin	160~400	39~390	200	
	高信赖性	RLS	小型化品,长寿命	85°C	3,000hrs	●	●	●	Pin	160~500	47~1,200	202
		RLB	尺寸缩小,长寿命,高纹波,低温度	85°C	3,000hrs	●	●	●	Pin	400~500	82~1,000	205
		RLC	尺寸缩小,长寿命	85°C	5,000hrs	●	●	●	Pin	160~500	39~2,200	207
		TLA	尺寸缩小,长寿命,宽温度	105°C	3,000hrs	●	●	●	Pin	160~500	56~2,200	210
		TLS	尺寸缩小,长寿命,宽温度,高纹波	105°C	3,000hrs	●	●	●	Pin	160~500	56~3,300	213
		TLG	尺寸缩小,长寿命,高纹波,低温度	105°C	3,000hrs	●	●	●	Pin	160~500	47~2,700	216
TLJ		尺寸缩小,长寿命,高纹波,低温度	105°C	3,000hrs	●	●	●	Pin	400~500	56~680	219	
TLC(LXG)		小型化品,长寿命	105°C	5,000hrs	●	●	●	Pin	10~500	47~47,000	221	
特殊用途	TLB	小型化品,长寿命	105°C	7,000hrs	●	●	●	Pin	160~500	47~2,200	225	
	UDA	宽温度	125°C	1,000hrs	●	●	●	Pin	16~250	100~10,000	228	
	RVA	无火花直流过电压	85°C	2,000hrs	●	●	●	Pin	200~450	47~2,200	230	
	TVA	无火花直流过电压	105°C	2,000hrs	●	●	●	Pin	200~450	56~1,800	232	
一般用途	DL	一般音频	85°C	2,000hrs	●	●	●	Pin	50~100	3,300~22,000	234	
	AHS	微型高保真音频	85°C	2,000hrs	●	●	●	Pin	50~100	3,300~22,000	235	
螺丝端子型	TGA(KMH)	标准品,宽温度	105°C	2,000hrs	●	●	●	螺丝	10~450	180~680,000	237	
	RGB	高纹波,高电压	85°C	2,000hrs	●	●	●	螺丝	16~600	100~680,000	241	
	RFC(RWF)	高纹波,长寿命	85°C	5,000hrs	●	●	●	螺丝	350~550	1,500~22,000	244	
	RFA	高纹波,长寿命	85°C	8,000~20,000hrs	●	●	●	螺丝	350~550	1,000~22,000	246	
	TFA	高纹波,长寿命	105°C	2,000~5,000hrs	●	●	●	螺丝	350~550	1,000~22,000	248	
	特殊用途	PH	闪光灯用	5~35°C	5,000times	●	●	●	Pin/螺丝	330	165~2,000	250
DH	焊接机用	40°C	1,000,000 Times	●	●	●	螺丝	315, 475	100~330	251		