


Features

VET (Vina EDLC High Temperature)

- Short-term Peak Power assist applications
- Over 500,000 cycle life (semi-permanent)
- Long-term reliability improved at high temperature and humidity
- RoHS compliant
- High Power Density



Drawing



Size	1325
D (Φ)	12.5 +1.0 Max
L (mm)	25.0 ±1.5
d (Φ)	0.7 ±0.1
P (mm)	5.0 ±0.5

Specification

Item	Characteristics	
Rated Voltage (V_R)	2.7V	
Operating Temperature	-40 ~ +85°C	
Capacitance Tolerance	-10 ~ +30%	
High Temperature & High Humidity Load Life	After 1,000 hours at V_R loaded under +85°C, 85%RH Humidity, capacitors meet the following criteria.	
	Capacitance Change	≤ 30% of initial value
	ESR	≤ 3 times of specified value
Cycle Life Characteristics	Cycle	Over 500,000
	ΔC	≤ 30% of initial value
	ESR	≤ 3 times of specified value
	Method	Cycle of Charge/discharge from V_R to $1/2V_R$
Shelf Life	2 Years No Electrical Charge, Temperature below 70°C (ΔC : ≤ 10% of initial value / ΔESR : ≤ 50% of specified value)	

Part Number	Rated Voltage (V)	Rated Capacitance (F)	ESR _{AC} (mΩ)	ESR _{DC} (mΩ)	Max Current (A)	Leakage Current (mA)	Weight (g)
VET2R7156QG	2.7 Surge Voltage (3.0V)	15 @ 25°C	40 @ 25°C 1kHz	60 @ 25°C 10msec	10.5 @ 25°C	0.040 @ 25°C 72hr	4.5±0.2

* Max. Current : 1 sec. discharge to $1/2V_R$

* Note: The products are tested based on the test conditions and methods defined in AEC-Q200