



## Features

### EDLC (Electric Double Layer Capacitor)

- High Power Density
- Over 500,000 cycle life (semi-permanent)
- Short-term Peak Power assist applications
- RoHS compliant
- Long-term reliability improved at high temperature and humidity



## Drawing



D ( $\Phi$ )	8.0 +1.0 Max
L (mm)	20.0 ±1.5
d ( $\Phi$ )	0.6 ±0.1
P (mm)	3.5 ±0.5

## Specification

Item	Characteristics	
Product series	EDLC	
Rated Voltage ( $V_R$ )	2.7V	
Operating Temperature	-40 ~ +65°C	
Capacitance Tolerance	-10 ~ +30%	
High Temperature Load Life	After 1,000 hours at $V_R$ loaded under +65°C, capacitors meet the following criteria.	
	Capacitance Change	≤ 30% of initial value
	ESR	≤ 2 times of specified value
Cycle Life Characteristics	Cycle	Over 500,000
	△C	≤ 30% of initial value
	ESR	≤ 2 times of specified value
	Method	Cycle of Charge/discharge from $V_R$ to 1/2 $V_R$
Shelf Life	3 Years No Electrical Charge, Temperature below 25°C (△C : ≤ 10% of initial value / △ESR : ≤ 50% of specified value)	

Part Number	Rated Voltage (V)	Capacitance (F)	ESR (mΩ)		Max. Current (A)	Leakage Current (mA, 72hr)	Size (mm) D x L
			AC(1kHz)	DC			
WEC 2R7 335 QG	2.7	3.3	80	140	3.0	0.007	08 x 20

\* Max. Current : 1 sec. discharge to 1/2 $V_R$

Version 1.3 2021.02.01.