



PACIFIC AUTOFUSE SERIES PACIFIC MINIFUSE SERIES

DIMENSIONS :



Unit : mm

DIMENSIONS :



Unit : mm

ELECTRICAL CHARACTERISTICS :

% of Ampere Rating	Opening Time	
	Minimum	Maximum
110%	100 hours	-
135%	0.75 sec	1800 sec
200%	0.15 sec	5 sec
350%	0.04 sec	0.5 sec
600%	0.02 sec	0.2 sec

* Fuse Characteristic may vary according to the conditions under which they are used.

Ampere Rating : 1 - 40A

Voltage Rating : DC 32V or less

DESIGN STANDARDS :

* SAE (Society of Automotive Engineers) J1284

APPROVALS :

* Recognised under the Components Program of Underwriters Laboratories Guide JFHR2, File No. E56412 [3A - 40A]

Please contact Pico for the other Ampere Ratings, Engineering Specification, additional technical and environmental data.

ELECTRICAL CHARACTERISTICS :

% of Ampere Rating	Opening Time	
	Minimum	Maximum
110%	100 hours	-
135%	0.75 sec	1800 sec
200%	0.15 sec	5 sec
350%	0.04 sec	0.5 sec
600%	0.02 sec	0.2 sec

Ampere Rating : 2 - 30A

Voltage Rating : DC 32V or less

DESIGN STANDARDS :

* SAE (Society of Automotive Engineers) J2077