



## FEATURES

- High Power Density
- Over 500,000 cycle life (semi-permanent)
- 2 units serially connected to provide 6.0V products
- RoHS compliant
- Long-term reliability improved at high temperature and humidity



## Drawing



D = 8.5mm, d=0.6mm

TYPE	I	O	H
P	4.5	12.9	8.5

(Unit : mm)

## SPECIFICATION

ITEM		CHARACTERISTICS	
Product series		EDLC 2 SERIAL MODULE	
Rated Voltage ( $V_R$ )		6.0V	
Operating Temperature		-40 ~ +65°C	
Capacitance Tolerance		-10 ~ +30%	
High Temperature Load Life		After 1,000 hours at $V_R$ loaded under +65°C, capacitors meet the following criteria.	
		Capacitance Change	≤ 30% of initial value
		ESR	≤ 2 times of specified value
Cycle Life Characteristics	Cycle	Over 500,000	
	$\Delta C$	≤ 30% of initial value	
	ESR	≤ 2 times of specified value	
	Method	Cycle of Charge/discharge from $V_R$ to $1/2V_R$	
Shelf Life		3 Years No Electrical Charge, Temperature below 25°C ( $\Delta C$ : ≤ 10% of initial value / $\Delta ESR$ : ≤ 50% of specified value)	

Part Number	Rated Voltage (V)	Capacitance (F)	ESR (mΩ)		Max. Current (A)	Leakage Current (mA, 72hr)		Size (mm) D x W x L
			AC(1kHz)	DC		@5.4V	@6.0V	
WEC6R0155QG	6.0	1.5	155	255	3.5	0.007	0.010	8.5x17x22

\* Max. Current : 1 sec. discharge to  $1/2V_R$

\* When do module more than 2 series, please fully discharge over 1 hour first, then assemble right after within 1 hour.