BWVN Series



BWVN series, an automatic assembly power inductor, is suitable for the portable DC-DC converter application.


Features

- RoHS compliant
- Highly accurate dimensions can be mounted automatically
- Terminals are highly resistant to pull forces.
- Highly reliable in environments of sudden temperature change


Applications

- Portable equipment such as, PDA,MP3,HDD, Mobil phone, DSC etc.
- Game Console.
- DC / DC converters.


Product Identification



Shapes and Dimensions



Recommended Pattern



Dimensions in mm

TYPE	Α	В	С	D	Н	1	J
BWVN00322515	3.2±0.2	2.5±0.2	1.5±0.2	1.0	2.6	1.2	1.0



SMD Unshielded Power Inductors - BWVN Series

Electrical Characteristics

Part Number	Inductance (uH)	Tolerance (±%)	Test Frequency (MHz)	RDC (Ω) ±20%	Isat (A)Max	Irms (A)Max	Marking	
BWVN00322515R47_00	0.47	30	1	0.030	3.40	2.55	R47	
BWVN003225151R0_00	1.0	30	1	0.045 2.30		2.05	1R0	
BWVN003225151R5_00	1.5	30	1	0.057	1.75	1.75	1R5	
BWVN003225152R2_00	2.2	20, 30 1		0.076	1.55	1.60	2R2	
BWVN003225153R3_00	3.3	20, 30	1	0.12	1.25	1.20	3R3	
BWVN003225154R7_00	4.7	20, 30	1	0.18 1.00		1.00	4R7	
BWVN003225156R8_00	6.8	20, 30	1	0.24	0.85	0.85	6R8	
BWVN00322515100 <u>0</u> 00	10	20, 30	1	0.38	0.75	0.70	100	
BWVN00322515150_00	15	20, 30	1	0.70	0.55	0.50	150	
BWVN00322515220 <u>0</u> 00	22	20, 30	1	0.81	0.50	0.45	220	
BWVN00322515330_00	33	20, 30	1	1.05	0.36	0.32	330	
BWVN00322515470_00	47	20, 30	1	1.48	0.28	0.24	470	


Note: When ordering, please specify tolerance code. Tolerance: $M=\pm20\%$, $T=\pm30\%$


- Operating temperature range 40°C ~ 125°C(Including self temperature rise)
- Isat for Inductance drop 30% from its value without current
- \bullet $\,$ Irms for a 40 $^{\circ}\mathrm{C}\,$ temperature rise from 25 $^{\circ}\mathrm{C}\,$ ambient with current
- Measure Equipment :
- L: Agilent/HP4287A+ Agilent/HP16197A, 1MHz 200mV

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent

Isat & Irms: Agilent HP4284A

Test Instruments: HP4287A Material/Impedance Analyzer









SMD Unshielded Power Inductors - BWVN Series

Packaging Specifications

Tape Dimensions



Reel Dimensions



Dimensions in mm

TYPE	Tape Dimensions								Reel Dimensions				Quantity	
ITPE	Α0	В0	K0	D	E	W	Р	P0	P2	Α	В	С	D	PCS / Reel
BWVN00322515	2.85	3.56	1.80	1.55	1.75	8	4	4	2	178	60	9	1.5	800

